



RECTORSEEK™ MID-TEMP AND RECTORSEEK™ LOW-TEMP Leak Locators

[Description](#) | [Characteristics](#) | [Applications](#) | [Packaging](#) | [Instructions](#) | [Precautions](#) | [Specifications](#) | [Limited Warranty](#)

DESCRIPTION:

RectorSeek™ Mid-Temp is a leak locator for use at normal temperatures (between 40 degree F and 200 degree F) on pipe or tank systems that contain gases. It can be used on oxygen systems.

RectorSeek™ Low-Temp is designed to detect leaks in colder temperature ranges (from -35 degree F to +200 degree F) on pipe and tank systems that contain gases. DO NOT use on oxygen systems.

[Top of Page](#)

CHARACTERISTICS:

- Longer bubbling action provides longer inspection periods
- Dauber or spray application methods available
- Easy to apply without any waste
- For Mid-Temp - can be used on oxygen, air, or gas
- For Low-Temp - for use at temperatures from -35 degree F to 200 degree F

[Top of Page](#)

APPLICATIONS:

RectorSeek™ Mid-Temp and RectorSeek™ Low-Temp are formulated for use on all types of pipe, tubing, valves, cylinders, tanks, pressure vessels, condenser/evaporator coils, refrigeration coils, and many other similar applications*. They can be used with freons and ammonia.

DO NOT use RectorSeek™ Low-Temp for oxygen leaks.

*Consult manufacturers for compatibility issues.

[Top of Page](#)

PACKAGING:

Mid-Temp Code	Low-Temp Code	Size	Qty. Per Case	Lbs. per Case	Cu. Ft Per Case
60633	61633	4 oz. dispenser spout (118 ml)	12 bottles	4	0.15
60554	61554	8 oz. dauber top (237 ml)	12 bottles	8	0.25
60434	61434	16 oz. spray gun (473 ml)	12 bottles	15	0.67
60435	61435	16 oz. refill (473 ml)	12 bottles	15	0.67
60273	61273	Gallon (3.8 L)	4 bottles	36	1.21
60151	61151	6 Gallon (27.7 L)	1 pail	57	1.52
60111	61111	55 Gallon (208 L)	1 drum	496	9.01

[Top of Page](#)

INSTRUCTIONS:

-
1. Apply leak locator directly on pressurized joint or seam to be tested.
 2. Bubbles will appear at location of leaking gas.
 3. After testing, wipe off and allow to air dry.

For additional technical information, call Toll Free 1-800-231-3345.

[Top of Page](#)

PRECAUTIONS:

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT,
CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

PRECAUTIONS: Do not take internally. May be harmful if swallowed in large quantities. May cause mild eye or skin irritation. Wear adequate protective gear and clothing. Avoid contact with eyes and skin. Wash after handling. **FIRST AID:** For any overexposure, get immediate medical attention after first aid is given. **Eyes** - Flush 15 minutes with clean water. **Skin** - Wash with soap and water. **Ingestion** - Only if conscious, give large amounts of water and INDUCE VOMITING. **FIRE AND SPILLS:** For fire, use water fog, CO2, foam or dry chemicals. Wipe up spills to prevent footing hazard. **STORAGE AND HANDLING:** Keep container closed when not in use. Do not reuse empty container. **KEEP OUT OF REACH OF CHILDREN.**

For additional information, refer to Material Safety Data Sheet.

[Top of Page](#)

SPECIFICATIONS:

	Mid-Temp	Low-Temp
Wt/Gal @ 77 degree F	8.35 +- .5 lbs/gal	8.50 +- .5 lbs/gal
Flash Point SETA CC	None	None
Color	Blue	Red
Shelf Life	2 years	2 years

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

[Top of Page](#)

LIMITED WARRANTY:

RectorSeal® makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RECTORSEAL®. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal® shall not be liable for incidental or consequential damages.

[Top of Page](#)

MANUFACTURED IN U.S.A. BY

RectorSeal®

2601 Spenwick Drive • Houston, TX 77055 USA
713-263-8001 • Fax 713-263-7577
Toll-free 800-231-3345 • Fax 800-441-0051

[Back to A/C Refrigeration Products](#)