

CODE NUMBER

3982604

DESCRIPTION

 $0.125~gpf,~Polished~Chrome~Finish,~Single~Flush,~Regal \@$ Exposed Manual Flushometer.

DETAILS

Flush Volume: 0.125 gpf (0.5 Lpf)Finish: Polished Chrome (CP)

• Valve: Diaphragm

Valve Body Material: Semi-red Brass

Fixture Type: UrinalFixture Connection: Top

• Rough-In Dimension: 11 ½" (292mm)

Spud Coupling: ³/₄" (19mm)
Supply Pipe: ³/₄" (19mm)

FEATURES

• ADA Compliant Metal Oscillating Non-Hold-Open Handle

Control Stop Plug

Sweat Solder Adapter with Cover Tube

• Cast Wall Flange with Set Screw

• Vacuum Breaker Flush Connection

• Spud Coupling Wall and Spud Flange for 3/4" Top Spud

 Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation

• 3/4" I.P.S. Wheel Handle Bak-Chek® Angle Stop



COMPLIANCES & CERTIFICATIONS















(WaterSense Listed, Satisfies LEED Credits, ADA Compliant, cUPC Certified, cUPC Green Certified, BAA Compliant, EPD)

RECOMMENDED SPECIFICATION

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

VALVE OPERATING PRESSURE (FLOWING)

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- Regal XL Exposed Installation Instructions
- Control Stop Repair and Maintenance Guide
- Flush Connections Flanges Repair and Maintenance Guide
- Tail Piece Repair and Maintenance Guide
- Regal Flushometers Repair and Maintenance Guide
- Additional Downloads

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the REGAL 186 product? View the general spec sheet with all options.

Find a compatible urinal for this flushometer.
Find a compatible water closet for this flushometer.



ROUGH-IN

