

## DESCRIPTION

Complete vitreous china hybrid urinal.

Model HYB-1000-A Code: 1001020 Waterfree Operation





## **SPECIFICATIONS**

#### Urinal

Model

· Wall hung, vitreous china

Vitreous China Hybrid Urinal

- · Complete mounting kit included
- · Patented high performance cartridge provides waterfree operation
- IAPMO certified to the applicable requirements in the following standards:
  - ASME A112.19.2/CSA B45.1
  - ASME A112.19.19
  - ASME A112.1.3

# Jetrinse<sup>™</sup> Assembly

- · Patented housing and drain line rinsing
- · Automatic activation injects 1 gallon of water through housing and drain line every 72 hours to prevent struvite build-up and prevent clogs
- IR switch for manual rinse activation
- · Long life lithium battery provides at least 8 years of service

#### Cartridge Assembly\*

- · Enhance patented design maximizes operational life, prevents accidental sealant loss and virtually eliminates odor
- Biodegradable sealant liquid
- Vandal resistant locking design
- · 20% less plastic than previous designs
- · Provides average of 7,000 uses that saves up to 40,000 gallons of water each year

\* Replacement cartridges sold separately

#### Features

- · Patented drain rinsing assembly
  - Eliminates number one cause of drain line clogs
  - Minimizes cleaning effort
  - Virtually eliminates odor
- Touch-free hygenic operation
- Earns maximum LEED credits
- Up to 5 times cleaner than convetional flush urinals
- Best in class odor control



Meets the American Disabilities Guidelines and ANSI A117.1 requirements when installed at the proper height requirements for accessibility.

## Product Specification

Hybrid urinal shall be made of vitreous china and provide waterfree operation. Urinal shall have a 2" NPT outlet connection. Urinal shall include automatic Jetrinse™ feature with 3/8" compression hose connection. Jetrinse<sup>™</sup> feature automatically cleans housing and drain every 72 hours with 1 gallon of water. Urinal shall be Sloan Model HYB-1000-A.





This space for Architect/Engineer approval		SLO
Job Name	Date	10500 Soumour
Model Specified	Quantity	Tio500 Seymour / Franklin Park, IL (
Variations Specified		Phone: 1-800-98 Fax: 1-800-447-
Customer/Wholesaler		sloanvalve.com
Contractor		
Architect		© 2015 Sloan Val



Avenue 60131 32-5839 8329

The information contained in this document is subject to change without notice

ve Company HYB-1000-A 08-14-15








Model HYB-1000-A Hybrid Urinal with Jetrinse<sup>™</sup> Solution Technology Vitreous China Hybrid Urinal

Description

Complete Vitreous China Hybrid Urinal with automatic drain rinse.

- Dimensions 26 3/4" (679 mm) x 19 5/8" (498 mm) x 14 3/8" (365 mm)
- Approximate Weight 68 lbs.
- Mounting For ADA Compliance For lip height of 17" (432 mm), distance from finished floor to drain centerline must be 9-3/4" (248 mm)
- Drain Connection and Material Installs on standard 2-inch drain connections with threaded nipple. Suitable DWV materials include cast iron, galvanized steel, ABS and PVC.


## IMPORTANT-Do not install on copper DWV due to copper's susceptibility to corrosion.




19 5/8" (498 mm)

- 16 5/8" (422 mm)

# **ROUGH-IN**



ROUGH-IN AND BRACKET LOCATION NOTE: All vitreous china dimensions shown in these drawings are nominal. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. Please take this into consideration when planning rough-in and plumbing layouts.



SIDE VIEW

FRONT VIEW

16 3/8" (416 mm)

# SLOAN VALVE COMPANY • 10500 SEYMOUR AVENUE • FRANKLIN PARK, IL 60131

Phone: 1-800-982-5839 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380 • www.sloanvalve.com

26 3/4" (679 mm)