

Location:

# SYMMONS® Laundry-Mate™

## Automatic Washing Machine Valve

W-400, W-500-B

### Specification Submittal



Model W-400



Model W-500-B

#### Model Numbers

- W-400 Valve assembly only
- W-500-B Valve assembly with enclosure

#### Options / Modifications

*Append appropriate -suffix to model number*

- IPSC Combination 1/2 inch MIPS or 1/2 inch sweat connections
- IPSF 1/2 inch FIPS connections

#### Warranty

- Limited Lifetime - to the original end purchaser in residential/consumer installations
- 5 years - for commercial installations

#### Feature Highlights

- Removes water supply pressure to limit danger of flooding from bursting supply hoses
- Single lever that works like a switch by automatically controlling both hot and cold water supply to machine
- Designed to withstand domestic water supply pressures
- 1/2 inch elbow sweat union connections
- Valve only for unfinished areas (model W-400)
- Attractive valve enclosure (model W-500-B)

#### Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05



# SYMMONS<sup>®</sup> Laundry-Mate<sup>®</sup>

the smart choice<sup>™</sup>

## Laundry-Mate Conceals Ugly Pipes and Hoses

- Eliminate wheel handle shut-offs
- Flush to wall cover
- Slide action on/off control
- Solid brass drain pan at outlet
- Paintable surface
- Easy to read operating



### Plumbing Behind the Wall

- 1-1/2" and 2" drain outlet
- Large metal mounting flanges
- Serviceable/replaceable valve
- Available with service stops



Washing Machine Valve and  
Drain Fixtures

### Reduces Wear on Hoses and Machine

The Laundry-Mate control valve has a unique, triple-seal packing, and features self-adjusting, spring-loaded, non-wearing action.

By eliminating constant water pressure shock, Laundry-Mate extends the life of your washing machine hoses.

### Simple to Install

Laundry-Mate installs easily between 2" x 4" studs on 16" centers with angle mounting straps (furnished). Copper tubing supplies enter the sides of the unit from above or below and attach to union elbows. Just connect the valve to the union elbows with two screws, install the drain pipe and hoses and screw on the cover - your work is done!



### Choose Between Two Models



#### W-600

Laundry-Mate Supply and Drain Fixture for 1/2" copper tubing and 1-1/2" drain

#### W-602

Laundry-Mate Supply and Drain Fixture for 1/2" copper tubing and 2" drain

#### Modification:

Suffix X: Service stops in W-600 or W-602

#### Dimensions:

Box: 8-1/4" x 5-1/2" x 3-3/4" deep

Cover: 9-1/4" x 6-1/2"

### Control Valves for Surface Mount Installations

These models are designed for basement areas, unfinished laundry rooms, or remodel work.



#### W-500-B

Valve with 1/2" sweat union ell connections and decorative cover



#### W-400

Valve with 1/2" sweat union ell connections

#### Modifications:

Suffix IPSC: 1/2" MIPS or 1/2" sweat connections

Suffix IPSF: 1/2" FIPS connections

All models feature the original washing machine valve manufactured by Symmons for over 30 years. For protection and assured quality, do not accept substitutes or valves that are not marked Symmons. All hoses and supply pipes shown herein are for illustration purposes only and are not included with the units.