For Residential Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

Series SW

Stop and Waste Shutoff Valves

Sizes: 3/8" - 3/4" (10 - 20mm)

Models


Model SWS – Sizes $\frac{3}{4}$ ", $\frac{3}{4}$ " (10, 15, 20mm) solder connections **Model SWC** – Sizes $\frac{1}{2}$ ", $\frac{3}{4}$ " (15, 20mm) compression ends **Model SWT** – Sizes $\frac{1}{2}$ ", $\frac{3}{4}$ " (15, 20mm) NPT female connections

Pressure — Temperature

Maximum pressure: 150psi (10.3 bars) WOG Maximum temperature: 180°F (82°C)







MODEL	SIZE (DN)		DIMENSIONS					WEIGHT		
			A		С		K			
	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
SWS	3/8	10	13/8	35	2 ¹⁵ / ₁₆	75	2	51	.5	.2
SWS	1/2	15	1 3⁄8	35	2 ¹⁵ / ₁₆	75	2	51	.5	.2
SWS	3/4	20	11/4	32	2 ¹⁵ ⁄ ₁₆	75	2	51	.5	.2
SWC	1/2	15	27/8	73	27//8	73	21/8	54	.5	.2
SWC	3/4	20	33/8	86	27/8	73	21/8	54	.6	.3
SWT	1/2	15	21/8	54	21/2	64	2	51	.4	.2
SWT	3/4	20	21/4	57	25/8	67	2	51	.8	.3

USA: 815 Chestnut St., No. Andover, MA 01845-6098; www.wattsreg.com **Canada:** 5435 North Service Rd., Burlington, ONT. L7L 5H7; www.wattscanada.ca





Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.